# CPI®-GRS-460-F

## **Food Grade Grease**



### **Description**

**CPI®-GRS-460-F** is a multi-purpose grease formulated using polyalphaolefin (PAO) base oil coupled with a calcium sulfonate thickener and a premium additive pacakee to deliver high performance and food grade purity.

Features of **CPI®-GRS-460-F** include a high dropping point, exceptional mechanical stability, and excellent resistance to water and corrosion. In addition, this grease has high load carrying performance and reduced wear.

**CPI®-GRS-460-F** is a multi-purpose grease designed for use in all food processing operations with recommended temperature -51°C to 204°C. **CPI®-GRS-460-F** is NSF H1 registered for lubricants with incidental food contact and is Kosher and Halal approved.

## **Applications**

- Food processing operations including mixing, stirring, baking, frying, cooking, freezing, cleansing, packaging, canning and bottling
- Applications requiring an incidental food contact grease

#### **Features and Benefits**

Water wash-out resistance Corrosion protection Food grade certified Reduced maintenance and reapplication Enhanced system reliability and reduced down-time NSF H1 certified for use within food processing environments



# **Typical Properties\***

Test Procedure	ASTM Test Method	CPI®-GRS-460-F
NLGI Grade	-	2
Grease Type	-	Calcium Sulfonate
Color	-	Tan
Penetration	D217	
Unworked		272
Worked 60 strokes		276
Dropping Point, °C	D2265	318
Four Ball Wear	D2266	
Average Scar Diameter, mm		0.45
Four Ball EP	D2596	
Weld Point, kg		400
Rust Protection	D1743	Pass
Oxidation Stability	D942	
Pressure drop after 100 hours, kPa		4
Water Washout, % Loss at 80°C	D1264	0.5
Oil Separation, % Loss	D1742	0.1
Bearing Life Performance, hours	D3527	280
Low Temperature Torque	D1478	
Start (-40°C)		4000
Running (60 min.)		600

<sup>\*</sup>These values are not intended for use in preparing specifications

**CPI Fluid Engineering** www.cpifluideng.com

#### North and South America

The Lubrizol Corporation 2300 James Savage Road Midland, MI 48642, USA

Telephone: 1 (989) 496-3780 Email: sales@cpifluideng.com

#### **Europe, Middle East and Africa**

Lubrizol Limited Pavilion One, Belasis Court Greenwood Road Stockton-on-Tees TS23 4AZ, UK

Telephone: +44 1642 565266 Email: euafricamesales@cpifluideng.com

#### Asia-Pacific

Lubrizol Southeast Asia (Pte) Ltd 44 Tanjung Penjuru Singapore 609032

Telephone: +65 6663 8684 Email: asiasales@cpifluideng.com

